Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-326-9833

Body Style:

Right angle type

Overall Length:

0.800 inches

Overall Width:

0.365 inches

Body Height:

0.336 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 1st contact grouping

Polarization Method:

Polarization wall

Connector Locking Method:

Friction

End Application:

Kidd class ddg; nimitz class cv; forrestal class cv; engine, aircraft tf-33-pw-102 (c-135e, ec-135h/k/p); landing craft air cushion (lcac);

oliver perry class ffg; arleigh burke class ddg; spruance class dd (963); ticonderoga class cg (47)

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end 1st contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Printed circuit single mating end 1st contact grouping

Included Contact Quantity:

7 single mating end 1st contact grouping

Included Contact Type:

Square pin single mating end 1st contact grouping

Special Features:

Contact position four is omitted; eight total positions; weapon system essential

Precious Material And Location:

Contact surfaces gold



Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.