NSN 5935-01-326-9833

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-326-9833

Body Style:
Right angle type
Overall Length:
0.800 inches
Overall Width:
0.365 inches
Body Height:
0.336 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Polarization Method:
Polarization wall
Connector Locking Method:
Friction
End Application:
Kidd class ddg; nimitz class cv; forrestal class cv; engine, aircraft tf-33-pw-102 (c-135e, ec-135h/k/p); landing craft air cushion (lcac);
oliver perry class ffg; arleigh burke class ddg; spruance class dd (963); ticonderoga class cg (47)
Terminal Location:
Side single mating end 1st contact grouping
Contact Material:
Copper single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end 1st contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Printed circuit single mating end 1st contact grouping
Included Contact Quantity:

7 single mating end 1st contact grouping

Included Contact Type:

Square pin single mating end 1st contact grouping

Special Features:

Contact position four is omitted; eight total positions; weapon system essential

Precious Material And Location:

Contact surfaces gold

NSN 5935-01-326-9833

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.