# NSN 5935-01-327-0958

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-327-0958 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Hood, top opening w/clamp **Overall Length:** 0.688 inches **Overall Height:** 1.359 inches **Overall Width:** 0.188 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 5 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Hood, top opening **Connector Locking Method:** Jackscrew **Connector Cable Strain Relief Method:** Cable clamp **Cable Opening Length:** 0.240 inches **Cable Opening Width:** 0.180 inches **Operating Tempurature Rating:** 500.0 degrees fahrenheit Thready Qty Per Inch (tpi): 56 **Thread Size:** 

0.086 inches **Terminal Location:** 

Back single mating end single contact grouping

# NSN 5935-01-327-0958

Electrical Plug Connector - Page 2 of 2



_							
r -	n	+-	rt.	NЛ	ate	ria	
·	OI.	ιca	·ι	IVI	alc	па	ı .

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum

**Shell Surface Treatment:** 

Anodize

## **Shell Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

### **Insert Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response single mating end

### **Included Contact Quantity:**

5 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

## **Precious Material:**

Gold and silver

#### **Thread Series Designator:**

Unc

### Shelf Life:

N/a

# **Unit Of Measure:**

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.