Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-327-3564

| Thread Class: | |
|---|---|
| 2a and 2b | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape | |
| Overall Length: | |
| Between 2.390 inches and 2.410 inches | |
| Overall Height: | |
| Between 0.675 inches and 0.695 inches | |
| Overall Width: | |
| Between 0.340 inches and 0.360 inches | |
| Environmental Protection: | |
| Shock resistant and vibration resistant and corrosion | resistant and humidity resistant and fungus resistant |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 3 rows of contacts non-inserted board single mating | and |
| Contact Removability: | |
| Nonremovable single mating end single contact grou | ping |
| Polarization Method: | |
| Jackscrew | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Operating Tempurature Rating: | |
| Between -65.0 degrees celsius and 125.0 degrees ce | alsius |
| Thready Qty Per Inch (tpi): | |
| 56 | |
| Thread Size: | |
| 0.086 inches | |
| Terminal Location: | |
| Back single mating end single contact grouping | |
| Contact Material: | |
| Copper alloy single mating end single contact groupi | ng |
| Contact Surface Treatment: | |
| Gold single mating end single contact grouping and r | nickel single mating end single contact grouping or gold single mating end single contact |
| grouping and copper single mating end single contact | |
| Insert Material: | |
| Plastic polyphenylene single mating end and glass fil | per single mating end |
| Contact Surface Treatment Specification: | |
| | n 1et treatment response single mating and single contact grouping and gg-p-200, cl 2 |

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping or mil-g-45204, type 2, cl 1, grade c military

NSN 5935-01-327-3564

Electrical Plug Connector - Page 2 of 2



Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end

single contact grouping

Included Contact Quantity:

62 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.062 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.