NSN 5935-01-327-8288

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-327-8288

Thread Class: 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 1.521 inches and 1.541 inches **Overall Diameter:** 1.476 inches **Environmental Protection:** Corrosion resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 17-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 and 115.0 and 240.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thread Length: 7.11 millimeters **Operating Tempurature Rating:** Between 65.0 degrees celsius and 175.0 degrees celsius Thready Qty Per Inch (tpi): 10 **Thread Size:** 25.0 millimeters and 1.188 inches **Thread Pitch In Millimeters:** 1.00

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-327-8288

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 2024
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Shell Material Specification:
Qq-a-225/6 federal specification single material response or qq-a-200/3 federal specification single material response
Thread Tolerance Class:
6g external
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Iso m and special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0

Mil-std (military Standard): Mil-g-45204 spec.