NSN 5935-01-327-8290

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-327-8290

view Offilite at https://aerobasegroup.com/hist//0300-01-021-0200
Body Style:
Straight shape
Overall Length:
1.800 inches
Overall Height:
0.450 inches
Overall Width:
0.665 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and moisture resistant and corrosion resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
Between 1.595 inches and 1.605 inches
Mating End Quantity:
1
Contact Removability:
Removable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl o military specification 1st treatment response single mating end 1st contact grouping and qq-n-290, cl 1 federal
specification 2nd treatment response single mating end 1st contact grouping
Terminal Type:

Crimp single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping or qq-b-626 federal specification single material response single mating end 1st contact grouping

Shell Material:

Aluminum alloy 6063

NSN 5935-01-327-8290

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 1 military specification single treatment response
Shell Material Specification:
Qq-a-200/9 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification single material response single mating end
Included Contact Quantity:
47 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.