

View Online at <https://aerobasegroup.com/nsn/5935-01-328-0979>

**Body Style:**

Angle shape, pcb type

**Overall Length:**

5.500 inches

**Overall Height:**

0.650 inches

**Overall Width:**

0.322 inches

**Environmental Protection:**

Salt spray proof and corrosion resistant and humidity resistant and vibration resistant and shock resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:**

0.097 inches

**Distance Between Mounting Facility Centers:**

5.300 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy 260 single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

V groove pin right-hand at 7: 30 oclock

**Shell Material:**

Aluminum alloy 6061 or aluminum alloy 6063

**Shell Surface Treatment:**

Chromate

**Shell Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Shell Material Specification:**

Qq-a-250/11, temper t6 federal specification 1st material response or qq-a-20019, temper t6 federal specification 2nd material response

**Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:**

100 single mating end single contact grouping

**Included Contact Type:**

Flat pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.100 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.