NSN 5935-01-328-1707

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-328-1707

Body Style:
Straight shape
Overall Length:
2.685 inches
Overall Height:
0.680 inches
Overall Width:
0.610 inches
Unthreaded Mounting Hole Diameter:
0.099 inches
Distance Between Mounting Facility Centers:
2.352 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
6625-01-226-5448 voltage standard
Operating Tempurature Rating:
Between -55.0 degrees celsius and 105.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:
Copper alloy
••

NSN 5935-01-328-1707

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Zinc and chromate
Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0