## NSN 5935-01-328-1710

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-328-1710

**Body Style:** 

Pcb, external coupling

**Overall Length:** 

Between 0.463 inches and 0.473 inches

**Overall Height:** 

Between 0.245 inches and 0.255 inches

**Overall Width:** 

Between 0.245 inches and 0.255 inches

**Environmental Protection:** 

Heat resistant and cold resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.155 inches and 0.205 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.155 inches and 0.205 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

Rf single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Push-pull

**End Application:** 

Intercommunication set, wireless, an/arc-187

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 165.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Shell Material:** 

Copper alloy 360

## NSN 5935-01-328-1710

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365, type 2, grade a federal specification single treatment response
Shell Material Specification:
Qq-b-626, 1/2 hard federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold and body surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0