NSN 5935-01-328-2723

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-328-2723 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 75.0 millimeters **Overall Diameter:** 67.0 millimeters **Environmental Protection:** Shock resistant and vibration resistant and waterproof **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 28-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **End Application:** 2350-01-305-0028 howitzer, medium, self-propelled **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 18

Thread Size:

1.438 inches

NSN 5935-01-328-2723

Electrical Plug Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping or rhodium single mating end single contact grouping or silver single mating end single
contact grouping
Insert Material:
Rubber chloroprene class cr single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Included Contact Quantity:
37 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold or contact surfaces rhodium or contact surfaces silver
Precious Material And Weight:
0.037 gold grains, troy or 0.037 rhodium grains, troy or 0.037 silver grains, troy
Precious Material:
Gold or rhodium or silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0