

View Online at <https://aerobasegroup.com/nsn/5935-01-328-2736>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 0.580 inches and 0.620 inches

**Overall Diameter:**

0.400 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Osm 2nd mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring and friction

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550 military specification 2nd treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-p-35 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Steel comp 303

**Shell Surface Treatment:**

Passivate

**Shell Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Shell Material Specification:**

Astm-a582 assn standard single material response

**Insert Material Specification:**

Mil-p-1946 military specification single material response all mating ends and I-p-403 federal specification single material response all mating ends

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.