

View Online at <https://aerobasegroup.com/nsn/5935-01-328-2745>

**Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:**

70.0 millimeters

**Overall Height:**

Between 56.7 millimeters and 57.3 millimeters

**Overall Width:**

Between 56.7 millimeters and 57.3 millimeters

**Environmental Protection:**

Shock resistant and vibration resistant and waterproof

**Unthreaded Mounting Hole Diameter:**

4.3 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 44.4 millimeters and 44.6 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 44.4 millimeters and 44.6 millimeters

**Cable Entrance Diameter:**

34.8 millimeters

**Distance From Mounting Shoulder To Front Face:**

Between 24.05 millimeters and 24.45 millimeters

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-6 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

73.0 single mating end 3rd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet slot

**Connector Cable Strain Relief Method:**

Compression nut

**End Application:**

2350-01-305-0028 howitzer, medium

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings or rhodium single mating end all contact groupings or silver single mating end all contact groupings

**Insert Material:**

Rubber chloroprene class cr single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings or qq-s-365 federal specification 3rd treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification all treatment responses

**Included Contact Quantity:**

3 single mating end 3rd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold or contact surfaces rhodium or contact surfaces silver

**Precious Material And Weight:**

0.051 gold grains, troy or 0.051 rhodium grains, troy or 0.051 silver grains, troy

**Precious Material:**

Gold or rhodium or silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.