

View Online at <https://aerobasegroup.com/nsn/5935-01-328-5423>

Body Style:

Pcb, external coupling

Overall Length:

1.375 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Environmental Protection:

Moisture resistant and vibration resistant and corrosion resistant and shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.900 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

4.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -55.0 degrees celsius and 85.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Mil-c-50 military specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel

Shell Material Specification:

Mil-c-50 military specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-50 spec.