NSN 5935-01-329-0910

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-329-0910 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.300 inches **Overall Height:** 1.031 inches **Overall Width:** 1.031 inches **Environmental Protection:** Vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.116 inches and 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** Between 0.708 inches and 0.728 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 12-dec single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Operating Tempurature Rating:** Between -54.0 degrees celsius and 176.5 degrees celsius

Thready Qty Per Inch (tpi): 20

NSN 5935-01-329-0910

Electrical Receptacle Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Gold single mating end single contact grouping Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Insert Material: Plastic epoxy single mating end Contact Surface Treatment Specification:
Plastic epoxy single mating end Contact Surface Treatment Specification:
Contact Surface Treatment Specification:
Mil-g-45204, type ii, class 2, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Steel comp 304l
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.