NSN 5935-01-329-1170

0.012 gold grains, troy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-329-1170

Body Style: Right angle type **Overall Length:** 1.200 inches **Overall Width:** 0.302 inches **Body Height:** 0.300 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Connector Locking Method:** Spring friction **Operating Tempurature Rating:** Between -40.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:** 12 single mating end single contact grouping **Included Contact Type:** Leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:**

NSN 5935-01-329-1170

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Specification Data:
28480-1251-5621 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.