

View Online at <https://aerobasegroup.com/nsn/5935-01-329-4208>

**Body Style:**

Straight shape

**Overall Length:**

1.460 inches

**Overall Height:**

1.425 inches

**Overall Width:**

0.360 inches

**Body Length:**

1.460 inches

**Environmental Protection:**

Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.100 inches

**Distance Between Mounting Facility Centers:**

1.300 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Connector Locking Method:**

Latch

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 120.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy 260 or copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester glass filled single mating end

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Contact Material Specification:**

Astm-b-122 assn standard 2nd material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519, ty gpt-15f, gpt-20f or gpt-30f military specification single material response single mating end

**Included Contact Quantity:**

14 single mating end single contact grouping

**Included Contact Type:**

Square pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-dtl-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-dtl-8305/25 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-24519 spec.