

View Online at <https://aerobasegroup.com/nsn/5935-01-329-4938>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/screw locks

**Overall Length:**

Between 2.140 inches and 2.160 inches

**Overall Height:**

0.965 inches

**Overall Width:**

Between 0.245 inches and 0.255 inches

**Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Connector Locking Method:**

Jackscrew-socket

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or gst-40f military specification 2nd material response single mating end

**Included Contact Quantity:**

36 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.036 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Specification Data:**

81349-mil-c-55302/63 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.