# NSN 5935-01-329-8690



Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-329-8690 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape w/center screw lock **Overall Length:** 2.210 inches **Overall Height:** 2.860 inches Diameter: 1.470 inches **Environmental Protection:** Vibration resistant and salt water resistant and humidity resistant **Cable Entrance Diameter:** Between 0.386 inches and 0.468 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Post jacksocket **Connector Cable Strain Relief Method:** Compression nut Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.190 inches

**Terminal Location:** 

Terminal Location:

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-329-8690

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 0, grade d military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

# **Shell Material:**

Metal

# **Shell Surface Treatment:**

Cadmium and chromate

#### **Shell Surface Treatment Specification:**

Mil-f-14072 military specification all treatment responses

## **Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end

#### **Included Contact Quantity:**

18 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.018 gold grains, troy

# **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-55181 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unf

## **Specification Data:**

81349-mil-c-5518/7 government specification

#### Shelf Life:

N/a

# **Unit Of Measure:**

## **Demilitarization:**

No

# Fiig:

A039b0