

View Online at <https://aerobasegroup.com/nsn/5935-01-330-2380>

Body Style:

Straight shape w/cable clamp

Overall Length:

1.140 inches

Bushing Diameter:

0.437 inches

Overall Height:

0.687 inches

Overall Width:

0.687 inches

Environmental Protection:

Vibration resistant and shock resistant and moisture resistant and corrosion resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.109 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.496 inches and 0.504 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.496 inches and 0.504 inches

Cable Entrance Diameter:

0.195 inches

Distance From Mounting Shoulder To Front Face:

0.550 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

4.0 gigahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.