## NSN 5935-01-330-3187

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-330-3187

**Body Style:** Straight shape **Overall Length:** Between 2.073 inches and 2.103 inches **Overall Height:** 0.649 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Mating End Quantity: Contact Position Arrangement Style:** 25 single mating end **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius **Insert Material:** Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end **Shell Material:** Metal **Shell Surface Treatment:** Cadmium

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification 1st material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military specification 2nd material response single mating end

**Test Data Document:** 

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-c-24308/4 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5935-01-330-3187

Electrical Receptacle Connector Body - Page 2 of 2



Der	nilit	ariz	atio	n:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.