

View Online at <https://aerobasegroup.com/nsn/5935-01-330-7169>

**Body Style:**

Straight shape

**Overall Length:**

0.954 inches

**Overall Height:**

3.110 inches

**Overall Width:**

2.000 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 2.778 inches and 2.788 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.432 inches and 1.442 inches

**Distance From Mounting Shoulder To Front Face:**

0.766 inches

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

"106, a106" all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Polarization Method:**

Mating end and 3 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Operating Temperature Rating:**

Between -54.2 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response all mating ends single contact grouping

**Terminal Type:**

Crimp all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification all treatment responses

**Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

**Included Contact Quantity:**

106 all mating ends single contact grouping

**Included Contact Type:**

Round pin all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.212 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.