## NSN 5935-01-330-8612

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-330-8612

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

3.156 inches

**Overall Height:** 

1.593 inches

**Overall Width:** 

0.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

2.913 inches

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

1.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

28.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**End Application:** 

6625-01-271-0224 counter, electrical

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Terminal Type:** 

Wire wrap single mating end single contact grouping

**Included Contact Quantity:** 

30 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

## NSN 5935-01-330-8612

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.030 gold grains, troy
Precious Material:
Gold
Specification Data:
28480-1251-5418 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0