

View Online at <https://aerobasegroup.com/nsn/5935-01-330-8691>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

2.488 inches

**Overall Height:**

0.455 inches

**Overall Width:**

Between 0.333 inches and 0.353 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.125 inches and 0.131 inches

**Distance Between Mounting Facility Centers:**

Between 2.148 inches and 2.164 inches

**Board Accommodated Length:**

1.843 inches single board and 1.907 inches single board

**Board Accommodated Width:**

Between 0.108 inches and 0.114 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Fixed inter-contact

**Connector Locking Method:**

Friction

**End Application:**

6665-00-136-5401 radio set

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Copper single mating end single contact grouping or nickel single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping or qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping and mil-g-45204, type 2, grade c, cl 1 military specification 3rd treatment response single mating end single contact grouping

**Terminal Type:**

Printed circuit single mating end single contact grouping

**Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f or gdi-30f military specification single material response single mating end or mil-m-24519, ty gpt-30f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

20 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.020 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-14550 spec.