Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-330-8767

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Rectangular shape center screwlock |
| Overall Length: |
| Between 1.975 inches and 2.005 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.718 inches |
| Overall Height: |
| 1.123 inches |
| Overall Width: |
| Between 1.062 inches and 1.092 inches |
| Environmental Protection: |
| Corrosion resistant and humidity resistant and thermal shock resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 108 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Polarization boss |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Post jacksocket |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| |



| Contact Surface Tre | patment: |
|------------------------|---|
| Gold single mating er | nd single contact grouping |
| Insert Material: | |
| Plastic polyester sing | le mating end and glass single mating end |
| Contact Surface Tre | eatment Specification: |
| Mil-g-45204 military s | pecification single treatment response single mating end single contact grouping |
| Terminal Type: | |
| Crimp single mating of | end single contact grouping |
| Contact Material Sp | ecification: |
| Qq-b-626, comp 2 fe | deral specification single material response single mating end single contact grouping |
| Shell Material: | |
| Steel comp 302 | |
| Shell Material Speci | fication: |
| Qq-s-766 federal spe | cification single material response |
| Insert Material Spec | ification: |
| Mil-m-24519, ty get-3 | Of military specification 1st material response single mating end and mil-p-46161, grade b, cl 3 military specification 2nd |
| material response sir | gle mating end |
| Included Contact Q | uantity: |
| 108 single mating en | d single contact grouping |
| Included Contact Ty | /pe: |
| Round pin single mat | ing end single contact grouping |
| Precious Material A | nd Location: |
| Contact surfaces gold | |
| Precious Material A | nd Weight: |
| 0.108 gold grains, tro | ру |
| Precious Material: | |
| Gold | |
| Thread Series Desig | jnator: |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military Sta | ndard): |
| Mil-g-45204 spec. | |