

View Online at <https://aerobasegroup.com/nsn/5935-01-330-8767>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Rectangular shape center screwlock

**Overall Length:**

Between 1.975 inches and 2.005 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.718 inches

**Overall Height:**

1.123 inches

**Overall Width:**

Between 1.062 inches and 1.092 inches

**Environmental Protection:**

Corrosion resistant and humidity resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

108 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Polarization boss

**Shell Type:**

Solid

**Connector Locking Method:**

Post jacksocket

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end and glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-626, comp 2 federal specification single material response single mating end single contact grouping

**Shell Material:**

Steel comp 302

**Shell Material Specification:**

Qq-s-766 federal specification single material response

**Insert Material Specification:**

Mil-m-24519, ty get-30f military specification 1st material response single mating end and mil-p-46161, grade b, cl 3 military specification 2nd material response single mating end

**Included Contact Quantity:**

108 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.108 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.