

View Online at <https://aerobasegroup.com/nsn/5935-01-330-9226>

Body Style:

Straight type

Overall Length:

Between 1.506 inches and 1.526 inches

Overall Height:

0.709 inches

Overall Width:

Between 0.245 inches and 0.255 inches

Unthreaded Mounting Hole Diameter:

0.106 inches

Distance Between Mounting Facility Centers:

Between 1.195 inches and 1.205 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

End Application:

5805-01-188-3993 central office, telephone, automatic

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45205 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

Key shape pin left-hand at 3 oclock and key shape pin right-hand at 3 oclock

Included Contact Quantity:

17 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.017 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45205 spec.