

View Online at <https://aerobasegroup.com/nsn/5935-01-330-9354>

**Body Style:**

Square flange mount

**Overall Length:**

Between 1.198 inches and 1.228 inches

**Overall Height:**

0.422 inches

**Overall Width:**

0.494 inches

**Unthreaded Mounting Hole Diameter:**

0.086 inches

**Threaded Device Type:**

Mounting hole

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

50.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 all mating ends all contact groupings

**Polarization Method:**

Shell

**Connector Locking Method:**

Screw or shell twistlock

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

0.006 all mating ends all contact groupings

**Terminal Location:**

Side all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Insert Material:**

Plastic polyester all mating ends

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw all mating ends all contact groupings

**Shell Material:**

Steel

**Shell Surface Treatment:**

Zinc

**Insert Material Specification:**

Mil-m-24519 military specification single material response all mating ends

**Included Contact Quantity:**

15 all mating ends all contact groupings

**Bushing Accommodation Hole Shape:**

Round

**Special Features:**

Female

**Precious Material And Location:**

Contacts gold

**Precious Material:**

Gold

**Supplementary Features:**

Mounting method - float

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-24519 spec.