

View Online at <https://aerobasegroup.com/nsn/5935-01-331-1009>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.359 inches

**Overall Height:**

1.578 inches

**Overall Width:**

1.578 inches

**Environmental Protection:**

Moisture proof

**Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.250 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.250 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.556 inches and 0.587 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

7 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

41.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Rubber chloroprene class cr single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

7 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.007 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.