NSN 5935-01-331-1013

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-1013

Body Style:

Straight shape, flush mount

Overall Length:

Between 1.094 inches and 1.124 inches

Overall Height:

Between 1.672 inches and 1.702 inches

Overall Width:

Between 3.360 inches and 3.390 inches

Unthreaded Mounting Hole Diameter:

Between 0.150 inches and 0.170 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.995 inches and 1.005 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.870 inches and 2.880 inches

Distance From Mounting Shoulder To Front Face:

Between 0.047 inches and 0.077 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

14 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic melamine single mating end or plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

NSN 5935-01-331-1013

Electrical Receptacle Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy 380.0 |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416 federal specification single treatment response |
| Shell Material Specification: |
| Qq-a-591 federal specification single material response |
| Insert Material Specification: |
| Mil-m-14 military specification all material responses single mating end |
| Included Contact Quantity: |
| 14 single mating end single contact grouping |
| Included Contact Type: |
| Coaxial pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.014 gold grains, troy and 0.014 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Specification Data: |
| 54933-100745 manufacturers specification control |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec |