Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-2806

Body Style:

Straight shape

Overall Length:

Between 3.195 inches and 3.205 inches

Overall Height:

Between 0.295 inches and 0.305 inches

Overall Width:

Between 0.195 inches and 0.205 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

End Application:

Tactical air operations module, an/tyq-2 (v) 1

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal

specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Tin and nickel

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification: Mil-t-10727, type 1 military specification 1st treatment response and qq-n-290 federal specification 2nd treatment response **Shell Material Specification:** Qq-b-626 federal specification single material response **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 64 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.064 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.