# NSN 5935-01-331-5870

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-5870

**Body Style:** 

Right angle type

**Overall Length:** 

0.530 inches

**Overall Width:** 

0.383 inches

**Body Height:** 

Between 0.310 inches and 0.340 inches

#### **Environmental Protection:**

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

# **Mating End Quantity:**

1

#### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

# **Connector Locking Method:**

Friction

# **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, type sdg-f or type gdi-30f military specification 1st material response single mating end or mil-m-24519, type gpt-30f or type gst-40f military specification 2nd material response single mating end

# **Included Contact Quantity:**

10 single mating end single contact grouping

Included Contact Type:

# NSN 5935-01-331-5870

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location:  |
|--|
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.010 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-c-55302/128 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
| Mil-std (military Standard):   |