

View Online at <https://aerobasegroup.com/nsn/5935-01-331-7640>

**Body Style:**

Straight type

**Overall Length:**

Between 2.590 inches and 2.610 inches

**Overall Height:**

0.408 inches

**Overall Width:**

Between 0.315 inches and 0.335 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.093 inches and 0.099 inches

**Distance Between Mounting Facility Centers:**

Between 2.345 inches and 2.355 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**End Application:**

Tactical air operations module an/tyq-2 (v) 1

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533, 1/4 ht federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-46174, cl 40, grade e military specification single material response single mating end

**Included Contact Quantity:**

51 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.051 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.