## NSN 5935-01-331-7645

Electrical Modular Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-7645

**Body Style:** 

Rectangular shape

**Overall Length:** 

6.230 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 5.640 inches and 5.660 inches

**Overall Height:** 

1.396 inches

**Overall Width:** 

Between 1.410 inches and 1.430 inches

**Unthreaded Mounting Hole Diameter:** 

0.160 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.580 inches and 0.600 inches

**Mating End Quantity:** 

1

**Contact Removability:** 

Removable single mating end all contact groupings

**Polarization Method:** 

Guide pin/socket

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**End Application:** 

Tactical air operations module an/tqy-2 (v) 1

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold and nickel or gold and copper single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate glass filled single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response and qq-n-290, cl 2 federal specification 2nd treatment response or mil-g-45204, type 2, cl 1, grade c military specification 3rd treatment response and mil-c-14550, cl 4 military specification 4th treatment response single mating end all contact groupings

**Terminal Type:** 

Solder well single mating end all contact groupings

**Contact Material Specification:** 

Qq-b-626 federal specification single material response or qq-b-750 federal specification single material response or qq-c-530 federal specification single material response single mating end all contact groupings

Shell Material:

Steel or aluminum

## NSN 5935-01-331-7645

Electrical Modular Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment:** Cadmium or copper alloy and anodize **Insert Material Specification:** Mil-m-14, sdg-f military specification single material response single mating end **Included Contact Quantity:** 6 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.080 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-std (military Standard):

Mil-g-45204 spec.

Fiig: A039b0