Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-8653

| Thread Class: |
|---|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Body Style: |
| Rectangular shape center screwlock |
| Overall Length: |
| Between 1.975 inches and 2.005 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.718 inches |
| Overall Height: |
| 1.449 inches |
| Overall Width: |
| Between 1.062 inches and 1.092 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 108 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Polarization boss |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew |
| Operating Tempurature Rating: |
| Between -54.0 degrees celsius and 125.0 degrees celsius |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| |

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 2 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 302

Shell Material Specification:

Qq-s-766 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

108 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.108 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.