## NSN 5935-01-331-9734

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-331-9734

**Body Style:** 

Right angle type

**Overall Length:** 

Between 8.190 inches and 8.210 inches

**Overall Height:** 

0.985 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.092 inches and 0.102 inches

**Distance Between Mounting Facility Centers:** 

Between 7.995 inches and 8.005 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

3 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

300.0 single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**End Application:** 

Tactical air operations module an/tyq-2 (v) 1

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy 260 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-611, half hard federal specification single material response single mating end single contact grouping

## NSN 5935-01-331-9734

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625, type 2, cl 2 military specification single treatment response
Shell Material Specification:
Qq-a-200/8, t6 federal specification single material response
Included Contact Quantity:
231 single mating end single contact grouping
Included Contact Type:
Flat pin single mating end single contact grouping
Special Features:
Furnished items - guide pin
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.231 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.