

View Online at <https://aerobasegroup.com/nsn/5935-01-332-2632>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

29.7 millimeters

Overall Height:

Between 23.5 millimeters and 24.1 millimeters

Overall Width:

Between 23.5 millimeters and 24.1 millimeters

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant and hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 15.09 millimeters and 18.26 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 15.09 millimeters and 18.26 millimeters

Distance From Mounting Shoulder To Front Face:

21.4 millimeters

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

13028 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 145.0 and 220.0 and 255.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Operating Temperature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Features Provided:

Color band engagement indicator

Thready Qty Per Inch (tpi):

10

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Stainless steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Special acme

Specification Data:

81349-dod-c-38999/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.