

View Online at <https://aerobasegroup.com/nsn/5935-01-332-3300>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Rectangular shape, w/jackscrew

Overall Length:

2.592 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.275 inches and 2.285 inches

Overall Height:

3.372 inches

Overall Width:

0.870 inches

Environmental Protection:

Corrosion resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.463 inches and 0.473 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

117 single mating end

Polarization Method:

Guide pin/socket

Connector Locking Method:

Jackscrew

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Guide Design And Location:

Key shape pin left-hand at 9 o'clock

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification 1st material response single mating end or mil-m-24519 military specification 2nd material response single mating end

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731/31 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.