

View Online at <https://aerobasegroup.com/nsn/5935-01-332-6559>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.125 inches

Overall Diameter:

2.219 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

32-22 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

110.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thread Length:

0.467 inches and 0.664 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 200.0 degrees celsius

Thready Qty Per Inch (tpi):

18 and 18

Thread Size:

2.000 inches and 2.000 inches

Insert Material:

Rubber silicone class q single mating end

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate and nickel

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response and qq-p-416, type 2, class 3 federal specification 2nd treatment response

Special Features:

In order to complete the connector assembly, the user must obtain/provide the backshell. Standard versions may be ordered as nsn 5935-01-193-5694, p/n m85049/52-1-12w for the straight style, or nsn 5935-01-216-3640, p/n m85049/51-1-32w for the right angle style

Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns and uns

Specification Data:

96906-ms3406 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.