NSN 5935-01-332-8413

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-332-8413 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.740 inches **Overall Height:** Between 0.490 inches and 0.510 inches **Overall Width:** Between 0.490 inches and 0.510 inches **Environmental Protection:** Vibration resistant and shock resistant and thermal shock resistant and corrosion resistant and moisture resistant and hermetic **Unthreaded Mounting Hole Diameter:** Between 0.092 inches and 0.112 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.330 inches and 0.350 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.330 inches and 0.350 inches **Distance From Mounting Shoulder To Front Face:** 0.310 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-332-8413

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatmen

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shell Material Specification:

Astm a484 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.