NSN 5935-01-332-9351

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-332-9351

Body Style:

Straight shape w/flange

Bushing Diameter:

Between 2.052 inches and 2.072 inches

Mounting Hole Circle Radius:

Between 1.240 inches and 1.260 inches

Overall Diameter:

Between 2.865 inches and 2.885 inches

Unthreaded Mounting Hole Diameter:

Between 0.178 inches and 0.198 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

L6-20 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -35.0 degrees fahrenheit and 120.0 degrees fahrenheit

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Plastic polyamide

Included Contact Quantity:

1 single mating end 3rd contact grouping

Included Contact Type:

Curved pin w/inside lip single mating end 3rd contact grouping

NSN 5935-01-332-9351

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Furnished items - protective cover
Specification Data:
11945-99ad1679-14 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0