NSN 5935-01-333-0065

Receptacle Dummy Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-0065
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
23.4 millimeters
Overall Height:
Between 28.3 millimeters and 28.9 millimeters
Overall Width:
Between 28.3 millimeters and 28.9 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant
and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 20.62 millimeters and 23.01 millimeters
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 20.62 millimeters and 23.01 millimeters
Distance From Mounting Shoulder To Front Face:
Between 20.9 millimeters and 21.4 millimeters
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0 and 124.0 and 152.0 and 219.0 and 265.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Operating Tempurature Rating:
Between -65.0 degrees celsius and 175.0 degrees celsius
Thready Qty Per Inch (tpi):
10
Thread Size:
0.875 inches
Shell Material:

Cadmium

Aluminum alloy

Shell Surface Treatment:

NSN 5935-01-333-0065

Receptacle Dummy Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

, , , , , , , , , , , , , , , , , , ,
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
On a sint a sure

Special acme

Specification Data:

81349-mil-c-38999/22 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.