NSN 5935-01-333-1240

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-1240

Body Style:

Straight shape

Overall Length:

1.080 inches

Overall Height:

0.390 inches

Overall Width:

Between 0.191 inches and 0.201 inches

Environmental Protection:

Thermal shock resistant and humidity resistant and heat resistant and cold resistant

Mating End Quantity:

4

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

NSN 5935-01-333-1240

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.