NSN 5935-01-333-1245

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-1245 **Thread Class:** 28 **Thread Direction:** Right-hand **Body Style:** Rectangular shape, w/jackscrew **Overall Length:** 2.592 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.280 inches **Overall Height:** 3.372 inches **Overall Width:** 0.870 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.468 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 117 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Post jacksocket Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:**

Back single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-01-333-1245

Electrical Receptacle Connector - Page 2 of 2



Terminal	Type:
----------	-------

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-h-14 military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

117 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Supplementary Features:

Mounting method - unthreaded hole

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731/32 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A039b0

Mil-std (military Standard):

Mil-h-14 spec.