# NSN 5935-01-333-2428

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-2428 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.425 inches **Overall Height:** Between 3.095 inches and 3.125 inches **Overall Width:** Between 1.985 inches and 2.015 inches **Environmental Protection:** Heat resistant and cold resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.122 inches **Distance From Mounting Shoulder To Front Face:** 0.766 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 8 1st mating end **Contact Removability:** Nonremovable all mating ends all contact groupings **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Post jacksocket **End Application:** Tactical air operations module an/tyq-2 (v) 1 **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.190 inches

Terminal Location:

Back all mating ends all contact groupings

# NSN 5935-01-333-2428

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material:**

Copper alloy all mating ends all contact groupings

#### **Contact Surface Treatment:**

Gold all mating ends all contact groupings

## **Insert Material:**

Plastic diallyl phthalate glass filled all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response all mating ends all contact groupings

## **Terminal Type:**

Solder well all mating ends all contact groupings

#### **Guide Design And Location:**

Hexagon shape female post left-hand at 12 oclock and hexagon shape female post right-hand at 12 oclock

## **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Cadmium and chromate

## **Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification all treatment responses

## **Shell Material Specification:**

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

## **Insert Material Specification:**

Mil-m-14, ty gdi-30f or sdg-f military specification 1st material response all mating ends or allied chemical 1288 bx mfr ref 2nd material response all mating ends or mil-m-14 military specification 3rd material response all mating ends

## **Included Contact Quantity:**

4 1st mating end single contact grouping

## **Included Contact Type:**

Round pin 2nd mating end 2nd contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.146 gold grains, troy

## **Precious Material:**

Gold

## **Thread Series Designator:**

Unc

#### Shelf Life:

N/a

## **Unit Of Measure:**

--

## Demilitarization:

No

# Fiig:

A039b0

## Mil-std (military Standard):

,