### NSN 5935-01-333-4275

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-4275

**Body Style:** 

Straight type

**Overall Length:** 

Between 3.890 inches and 3.910 inches

**Overall Height:** 

0.465 inches

Overall Width:

Between 0.340 inches and 0.360 inches

**Environmental Protection:** 

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

**Distance Between Mounting Facility Centers:** 

Between 3.640 inches and 3.660 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

3 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

1200.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Connector Locking Method:** 

Friction

**Operating Tempurature Rating:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 00 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

# NSN 5935-01-333-4275

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

92 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.092 gold grains, troy

#### **Precious Material:**

Gold

#### **Specification Data:**

86360-201c8566 manufacturers source control

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.