NSN 5935-01-333-6115

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-6115

Body Style:

Straight shape, external coupling

Overall Length:

0.902 inches

Overall Diameter:

1.343 inches

Distance From Mounting Shoulder To Front Face:

0.540 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

43 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

End Application:

5865-01-188-3309 jammer system, response

Operating Tempurature Rating:

Between -40.0 degrees celsius and 85.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

NSN 5935-01-333-6115

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.004 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0