Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-6116

Thread Class:
2a De de State
Body Style:
Straight shape, external coupling
Overall Length:
1.240 inches
Overall Diameter:
0.709 inches
Cable Entrance Diameter:
0.079 inches
Distance From Mounting Shoulder To Front Face:
0.807 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Bnc single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
End Application:
5865-01-188-3309 jammer system, response
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-333-6116

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.