NSN 5935-01-333-8112

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-333-8112 **Thread Class:** 2b and 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 2.328 inches **Overall Height:** 0.922 inches **Overall Width:** 0.953 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 1.016 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20-sep single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Shell Material:**

Anodize

Aluminum alloy

Shell Surface Treatment:

NSN 5935-01-333-8112

Electrical Receptacle Connector Body - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Shell Guide Type And Location Designator:

A slot

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.