NSN 5935-01-334-0991

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-334-0991 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.978 inches **Overall Diameter:** 1.067 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Distance From Mounting Shoulder To Front Face:** Between 0.701 inches and 0.711 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 7-oct single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 85.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** 5865-01-188-3309 jamming system, response **Operating Tempurature Rating:** Between -65.0 degrees celsius and 200.0 degrees celsius Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-334-0991

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-14072 military specification single treatment response or mil-a-8625, type 2, cl 1 military specification single treatment response
Shell Material Specification:
Qq-a-225 federal specification single material response
Included Contact Quantity:
7 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-g-45204 spec.

Mil-std (military Standard):

A039b0