

View Online at <https://aerobasegroup.com/nsn/5935-01-334-1343>

Thread Class:

2a and 2g

Thread Direction:

Left-hand and right-hand

Body Style:

Straight shape

Overall Length:

2.531 inches

Environmental Protection:

Chemical resistant and corrosion resistant and dust resistant and shock resistant and vibration resistant and humidity resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Ascc 16-325 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

16.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 90.0 and 180.0 and 243.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut or internally threaded coupling ring

Width Across Flats:

2.250 inches

Operating Temperature Rating:

Between -80.0 degrees fahrenheit and 225.0 degrees fahrenheit

Thready Qty Per Inch (tpi):

18 and 8

Thread Size:

1.613 inches and 2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.016 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Npt and acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0